



## CHEMICAL INDUSTRIES INC.

PHONE: (403) 571-7979  
FAX: (403) 571-7977  
TOLL FREE: 1-800-447-1437

### TECHNICAL DATA SHEET

**PRODUCT NAME:**

**SUPER GREASE TRAP & DRAIN OPENER**

**CODE: 7822**

**DESCRIPTION:**

**Super Grease Trap & Drain Opener** is a liquid treatment and odour control for grease traps, drain sumps, garbage and sewer areas. It is a concentrated degreaser that contains no petroleum or chlorinated solvents and is non-caustic and non-corrosive, thereby being biodegradable and environmentally safe.

**DIRECTIONS:**

**GREASE TRAPS:** A 21 gallon (96 litre) capacity trap is treated as follows:

**Initially:**

1. Manually clean the trap.
2. Pour one (1) gallon (4.5 litres) of product down a sink leading to the trap.
3. Flush with one (1) gallon (4.5 litres) of cold water.
4. Let stand for ½ hour.
5. Resume normal operations.

**Weekly:** When trap is at a low use period, add 16 ounces (½ litre) of product followed by an equal amount of water. Double this treatment once per month.

**NOTE: ADJUST TREATMENT ACCORDING TO SIZE OF TRAP AND WATER FLOW.**

**CLOGGED DRAINS:**

1. Add 32 – 64 ounces (1-2 litres) per square foot of pipe (Calculated at 1 square foot equals 2" pipe diameter X 6 ft.)
2. Let stand for one (1) hour.
3. Flush with cold water.

**NOTE: FOR HEAVY BUILD-UPS USE 1 – 2 GALLONS PER SQUARE FOOT.**